MDCE Series





FEATURES

- High satura on characteris c core for large satura on current and low loss.
- Closed magne c circuit design reduces leakage flux.
- High precision DCR.
- Halogen Free & ROHS compliant.
- Opera ng temperature: -40 to +125 °C

APPLICATION

- AI Servers, Data Centers, GPU/AI Accelerators.
- Desktop Motherboards, CPU/GPU Power Delivery.
- Mul -phase VRM, High-current DC-DC Converters.
- Networking Equipment, Communica on Infrastructure.






Series	A	B	C	D	E	F	a	b	c
MDCE060610	6.5 max	6.5 max	10.0 max	3.7±0.2	1.75 typ	2.75 typ	7.2	2.6	4.2
MDCE090510	9.0 max	5.2 max	9.5 max	2.4 typ	2.50 typ	3.70 typ	9.2	3.4	3.0
MDCE100710	10.0 max	7.0 max	10.0 max	2.4±0.2	2.70 typ	4.60 typ	11.0	4.4	3.0

:

Marking	Printing Inductance)

:



060610	330±1.0	100±1.0	13.2±0.5	24.5±0.2	
090510	330±1.0	100±1.0	13.2±0.5	24.5±0.2	
100710	330±1.0	100±1.0	13.2±0.5	24.5±0.2	

:

-
-
-
-
-
-
-